(19) World Intellectual Property **Organization**

International Bureau





(43) International Publication Date 3 November 2005 (03.11.2005)

PCT

(10) International Publication Number WO 2005/102634 A1

(51) International Patent Classification7:

B27L 1/02

(21) International Application Number:

PCT/FI2005/050108

(22) International Filing Date: 29 March 2005 (29.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

20045141

20 April 2004 (20.04.2004) \mathbf{FI}

- (71) Applicant (for all designated States except US): AN-DRITZ OY [FI/FI]; Tammasaarenkatu 1, FI-00180 Helsinki (FI).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): KOKKO, Pekka [FI/FI]; Pähkinätie 31, FI-16710 Hollola (FI).
- LEITZINGER OY; Tammasaarenkatu 1, (74) Agent: FI-00180 Helsinki (FI).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: DEBARKING MECHANISM



(57) Abstract: The invention relates to a debarking mechanism (1) for the excortication or pretreatment of trees (2) for separately performed final barking and for the expulsion of at least some of the removed barks from a wood flow passing through the debarking mechanism, said debarking mechanism comprising a number of rotatable debarking shafts (3, 3') extending parallel to an advancing direction (A) of the trees (2) to be fed therethrough, which are provided with a number of teeth (4) extending beyond the circumferential surface of the shaft (3, 3') and adapted to strip bark off the presently processed trees (2) transversely to the lengthwise direction of the trees and at the same time to convey the trees transversely relative to said shafts (3, 3'), and said shafts (3, 3') together with the teeth thereof (4), being adapted to constitute at least a section of a support surface, upon which the presently processed trees (2) travel through the debarking mechanism (1), and said debarking shafts (3, 3') being adapted to each other in such a way that the presently processed trees (2) make a circular motion (C) in the debarking mechanism, in which motion the trees (2) are forced upon the support surface constituted by the debarking shafts (3, 3') effected by the rotatory motion (5) of the debarking shafts (3, 3') in their turn into the upper position, from

which they roll down above the other trees (2) in the debarking machine (1) into the lower position. The uppermost debarking shaft (3') has been fitted together with a guiding surface (8), said surface together with the uppermost debarking shaft (3') forming a slot (9) convergent in the direction of rotation (5) of the debarking shaft (3').

WO 2005/102634 A1



 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.